CC31xx SLS Email Demo Application

Overview and application details

This sample applications demonstrates how CC3100 can be used to send an email over SMTP. The application configures CC3100 to connect w/ an SMTP server and sends email to it. SMTP server forwards it to the recipient's email-server and the recipient receives the email from his email-server using IMAP/POP3 and/or other proprietary protocol.

Note: This wiki page is only applicable for **CC3100-SDK v1.0.0** and upward releases. For documentation on older SDKs' examples, refer corresponding file in **<cc3100-sdk-installation-location>\cc3100-sdk\docs\examples**

Email application's sequence

- Client first makes a TCP connection with SMTP server.
- SMTP server replies back w/ response-code and greeting-message containing FQDN
- HELO/EHLO – Client sends Hello Message to the server. ESMTP accepts EHLO
- The SMTP server replies with Code 250 and Hello Message. ESMTP Server replies with SMTP extensions it supports such as Email maximum Size, authentication etc.
- If SMTP server requires authentication, the client sends "auth login" followed by "Username" and "Password" encoded with proper encryption accepted by SMTP Server.

  auth login

  334 VXNlcm5hbWU6

- Client sends "Username" encoded with proper encryption accepted by SMTP server

  a2F1c2hmmdmdmdmhbGt1a2thckBnhfjdhfdjjsksbWFpbC5jb20

- Client sends "Password" encoded with proper encryption accepted by SMTP Server

  334 UGFzc3dvcmQ6

  Mlklkdldldl21haWxhYjskjdkskjss2Mzc3M=

- SMTP server replies with Authentication Success/Failure.

  535 Incorrect authentication data/ 235 Authentication Successful

- SMTP client then sends From-Address

  MAIL FROM: xyz@abc.com

- SMTP client sends To-Address

  RCPT TO: abc@ti.com

- SMTP client sends DATA command

  DATA

- SMTP client sends email data.
- SMTP server responds with the acknowledgement

Source Files briefly explained

1. main - Initializes the device, connects to an access-point and configures the email
2. email - Wrapper functions to connect to SMTP-Server and send the configured email. These functions are called from main
3. base64 - Functions to convert the raw bytes in quasi-big-endian order to Base64 string

Usage

Prerequisite: Internet connectivity is required to work w/ this sample application

- Open **config.h** and change values for **USER** and **PASS** for setting up the source email.

```
CC3100 will try to establish connection w/ this AP when instructed by the user.
Ensure the access-point has internet connectivity
```

- Compile and run the application using Visual-Studio or Eclipse
- User will be prompted to configure the AP parameters for establishing a Wi-Fi connection
- Enter **01** to connect to the configured AP

```
This is the AP that was configured above
```

- Enter **03,<destination email>,<subject>** to set the destination e-mail address and subject
- Enter **04,<message>**
- Enter **05** to send the email
- On success, below message will be displayed on the console

Limitations/Known Issues

- The size of the message is currently 64.
- Subject should be less that 30 characters
- Destination email should be less that 30 characters.

Article Sources and Contributors

CC31xx SLS Email Demo Application *Source*: http://processors.wiki.ti.com/index.php?oldid=193658 *Contributors*: A0131814, A0132173, A0221015, Codycooke, Malokyle, Raghshenoy

Image Sources, Licenses and Contributors

File:Cc31xx cc32xx return home.png *Source*: http://processors.wiki.ti.com/index.php?title=File:Cc31xx_cc32xx_return_home.png *License*: unknown *Contributors*: A0221015
File:Cc31xx return sample apps.png *Source*: http://processors.wiki.ti.com/index.php?title=File:Cc31xx_return_sample_apps.png *License*: unknown *Contributors*: A0221015
Image:Scrshot_sls_email.png *Source*: http://processors.wiki.ti.com/index.php?title=File:Scrshot_sls_email.png *License*: unknown *Contributors*: Raghshenoy